Applicant(s): Masayuki Tobita et al., Attorney Docket No.: 65901-014001/ P1P2003172US

Serial No. : 10/686,384 Filed : October 14, 2003

Page : 2 of 7

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application.

<u>Listing of Claims</u>:

1-12. (Cancelled)

13. (Currently Amended) A mold product comprising a liquid crystal composition for conducting heat, $\frac{1}{2}$ said liquid crystal composition containing liquid crystal polymer having an orientation degree α obtained by equation 1 below,

Orientation degree $\alpha = (180-\Delta\beta)/180$ equation 1

in which $\Delta\beta$ is a half width in an intensity distribution obtained by fixing peak scattering angle in X-ray diffraction measurement and by varying the azimuth angle from 0 to 360 degrees;

wherein said orientation degree α is in a range between 0.5 and 1.0, and said liquid crystal composition contains heat conductive filler of less than 100 parts by weight with respect to 100 parts by weight said liquid crystal polymer.

Applicant(s): Masayuki Tobita et al., Attorney Docket No.: 65901-014001/P1P2003172US

Serial No. : 10/686,384 Filed : October 14, 2003

Page : 3 of 7

14. (Currently Amended) A mold product comprising a liquid crystal composition for conducting heat, siad said liquid crystal composition containing liquid crystal polymer having an orientation degree α obtained by equation 1 below,

Orientation degree $\alpha = (180-\Delta\beta)/180$ equation 1

in which $\Delta\beta$ is a half width in an intensity distribution obtained by fixing peak scattering angle in X-ray diffraction measurement and by varying the azimuth angle from 0 to 360 degrees;

wherein said orientation degree α is in a range between 0.5 and 1.0; and the liquid crystal polymer is an aromatic polyester containing 80 mol% 4-hydroxybenzoic acid and 20 mol% mixture of terephthalic acid and ethylene glycol, or the liquid crystal polymer is an aromatic polyester containing 60 mol% 4-hydroxybenzoic acid and 40 mol% mixture of terephthalic acid and ethylene glycol.

- 15. (New) A mold product according to claim 13 wherein the liquid crystal polymer is a thermotropic liquid crystal polymer that exhibits melt phase having optical anisotropic property.
- 16. (New) A mold product according to claim 13 wherein said thermotropic liquid crystal polymer comprises a polymer selected from a group consisting of full aromatic polyesters and full aromatic polyesteramides.
- 17. (New) A mold product according to claim 13 wherein said liquid crystal polymers were provided with an orientation degree α by applying a magnetic force generated by a magnetic field generating device.
- 18. (New) A mold product according to claim 13 wherein said mold product is formed into a sheet shape and the orientation degree .alpha. of the liquid crystal polymers at least in a direction of the thickness is in a range between 0.5 and 1.0.

Applicant(s): Masayuki Tobita et al., Attorney Docket No.: 65901-014001/ P1P2003172US

Serial No. : 10/686,384 Filed : October 14, 2003

Page : 4 of 7

19. (New) A mold product according to claim 13 wherein a heat conductivity λ in at least one direction is in a range between 0.7 W/(m·K) and 20 W/(m·K).

- 20. (New) A mold product according to claim 14 wherein the liquid crystal polymer is a thermotropic liquid crystal polymer that exhibits melt phase having optical anisotropic property.
- 21. (New) A mold product according to claim 14 wherein said thermotropic liquid crystal polymer comprises a polymer selected from a group consisting of full aromatic polyesters and full aromatic polyesteramides.
- 22. (New) A mold product according to claim 14 wherein said liquid crystal polymers were provided with an orientation degree α by applying a magnetic force generated by a magnetic field generating device.
- 23. (New) A mold product according to claim 14 wherein said mold product is formed into a sheet shape and the orientation degree .alpha. of the liquid crystal polymers at least in a direction of the thickness is in a range between 0.5 and 1.0.
- 24. (New) A mold product according to claim 14 wherein a heat conductivity λ in at least one direction is in a range between 0.7 W/(m·K) and 20 W/(m·K).